

LUXOL A/S

Tangrimme 19, Kløv Kær DK - 7700 Thisted

Tel. +45 97 99 51 66 www.luxol.dk luxol@luxol.dk CVR/VAT: DK 29 42 43 73

Product Data Sheet

04.11.2019

Product: Luxovit 1.0-1.5 mm

TYPICAL CHEMICAL ANALYSIS:

Description:

Luxovit is calcined flint. Calcined means that the raw flint has been heated up to 1100 degrees C. and this treatment makes the dark blue flint almost white. The product can be delivered either in small 25 kg plastic bags on pallets or in big bags on pallets.

GRADING:

SiO ₂		97,0%				Above 2	.0 mm	0%		
Na ₂ O		0,3%				Above 1	Above 1.4 mm		x 25%	
K ₂ O		0,3%			Below 1	.0 mm	0 mm max 1			
MgO	MgO			Below 0.5 mm					1%	
CaO	CaO									
Fe ₂ O ₃	Fe ₂ O ₃		<u>%</u>							
Al_2O_3	Al ₂ O ₃									
PSV	PSV 5									
-						5.	- 10		-	
Luxovit:		-								
Supplied t	o:									
Against purchase order:					has b	een tested a	nd compli	es with our s	specifications.	
	Cont. no.:				Seal no.:					
Lot content spec.										
No.	Pack	aging		From week/yea	r	Weight in k	Veight in kg		Weight in total	
	-								0	
	-	-							0	
	-								0	
									0	