

LUXOL A/S

Tangrimme 19, Kløv Kær DK - 7700 Thisted

Tel. +45 97 99 51 66 www.luxol.dk luxol@luxol.dk CVR/VAT: DK 29 42 43 73

Product Data Sheet

30.10.2019

Product: Luxovit 1.6-2.5 mm

TYPICAL CHEMICAL ANALYSIS:

Description:

Luxovit is calcined flint. Calcined means that the raw flint has been heated up to 1100 degrees C. and this treatment makes the dark blue flint almost white. The product can be delivered either in small 25 kg plastic bags on pallets or in big bags on pallets.

GRADING:

6:0	1	07.00/				10/	
SiO ₂		97,0%				max 1%	
Na ₂ O		0,3%		Above 2.0 mm 60-90%			
K ₂ O		0,3%		Below 1.4 mm max 15%			
MgO		0,3%		Below 1.0 mm max 5%			
CaO	CaO						
Fe ₂ O ₃		0,2%					
Al_2O_3	Al ₂ O ₃						
		0,6%			经验		
PSV		56	56				
=							
Luxovit:		-					
Supplied to:							
Against purchase order:		ler:		has been to	ested and compli	ies with our specifications	
Cont. no.:		o.:		Seal no.:			
Lot content spec.							
No.		ackaging	From week/yea	r Wei	ght in kg	Weight in total	
	_					0	
						0	
						0	
						0	